

SAFETY DATA SHEET

KUMANOX-3111 F

Date of issue: 2015-05-19

Revision date: 2018-08-30

Version: R0003.0001

General use: Additive for paint, polymer additive, antioxidantRestriction on use: Not availableHanufacturer / Supplie: / Stributor informationOmanufacturer informationOmanufacturer information- Company name: Kumho Petrochemical Co., Ltd Address: 227 Yeosusandan 2-ro Yeosu-si Jeollanam-do, Korea- Dept.: Production Technology Team- Telephone number: 482-61-688-3920- Emergency telephone number: +82-61-688-3931~4- Fax number: +82-61-688-3939- Fax number: kweo08@kkpc.comOmpany name: Address: kweo08@kkpc.comOmpany name: Address: keeo1688-3939: Address: keeo1688-3939: Dept.: keeo1688-3939: Emergency telephone number: keeo1688-3939: Emergency telephone number: keeo1688-3939: Emergency telephone number: keeo1688-3939: Dept.: keeo1688-3939: Emergency telephone number: keeo1688-3931: Dept.: keeo1688-3939: Dept.: keeo1688-3939: Dept.: keeo1688-3939: Dept.: keeo1688-3931: Dept.: keeo1688-3931 <th>roduct name</th> <th></th>	roduct name	
- Restriction on use : Not available Statuse : Statuse - Company name : Statuse - Ordpany name : Statuse - Statuse : Potoccion Conclusiony Conclus	KUMANOX-3111 F	
- Restriction on use Not available Company name Subno Percohemical Co., Ltd. - Company name Subno Percohemical Co., Ltd. - Address Subno Percohemical Co., Ltd. - Popta Subno Percohemical Co., Ltd. - Ponno Percohemical Co., Ltd. Subno Percohemical Co., Ltd. - Ponta Subno Percohemical Co., Ltd. - Popta Subno Percohemical Co., Ltd. -	ecommended use and rest	riction on use
C. Manufacturer / Supplier / Distributor information • Manufacturer informatio- • Company name : Kumho Petrochemical Co., Ltd. • Address : 227 Yeosusandan 2-ro Yeosu-si Jeollanam-do, Korea • Dept. : Production Technology Team • Telephone number : +82-61-688-3920 • Emergency telephone : +82-61-688-3931~4 • Ranumber : +82-61-688-3939 • E-mail address : kweeo08@kkpc.com • Company name : kweeo08@kkpc.com • Company name :	General use :	Additive for paint, polymer additive, antioxidant
Company name: Kumho Petrochemical Co., Ltd Address: 227 Yeosusandan 2-ro Yeosu-si Jeollanam-do, Korea- Dept.: Production Technology Team- Telephone number: +82-61-688-3920- Emergency telephone number: +82-61-688-3931~4- Fax number: +82-61-688-3939- E-mail address: kweo08@kkpc.com- Company name: kweo08@kkpc.com- Company name:- Company name:- Company name:- Company name:- Telephone number:- Dept.:- Dept.:- Telephone number:- Telephone number:- Telephone number:- Fax number:- Telephone number:- Fax number:- Fax number:- Fax number:	Restriction on use :	Not available
Company name: Kumho Petrochemical Co., Ltd Address: 227 Yeosusandan 2-ro Yeosu-si Jeollanam-do, Korea- Dept.: Production Technology Team- Telephone number: +82-61-688-3920- Emergency telephone number: +82-61-688-3931~4- Fax number: +82-61-688-3939- E-mail address: kweo08@kkpc.com- Company name: kweo08@kkpc.com- Company name:- Company name:- Company name:- Company name:- Telephone number:- Dept.:- Dept.:- Telephone number:- Telephone number:- Telephone number:- Fax number:- Telephone number:- Fax number:- Fax number:- Fax number:	Ianufacturer / Supplier / E	Distributor information
- Address: 227 Yeosusandan 2-ro Yeosu-si Jeollanam-do, Korea- Dept.: Production Technology Team- Telephone number: +82-61-688-3920- Emergency telephone number: +82-61-688-3931~4- Fax number: +82-61-688-3939- E-mail address: kwseo08@kkpc.com• Supplier/Distributer information:- Company name:- Company name:- Address:- Dept.:- Dept.:- Telephone number:- Telephone number:- Emergency telephone number:- Telephone number:- Emergency telephone number:- Fax number:- Telephone number:- Fax number:- Fax number:- Telephone:- Telephone:- Fax number:- Fax number:	Manufacturer information	
- Dept.: Production Technology Team- Telephone number: +82-61-688-3920- Emergency telephone number: +82-61-688-3931~4- Fax number: +82-61-688-3939- E-mail address: kwseo08@kkpc.comSupplier/Distributer information: kwseo08@kkpc.com- Company name: Company name: Address: Dept.:- Telephone number: Telephone number: Emergency telephone number: Fax number: Fax number: Fax number: Fax number: Fax number: -	- Company name :	Kumho Petrochemical Co., Ltd.
- Telephone number: +82-61-688-3920- Emergency telephone number: +82-61-688-3931~4- Fax number: +82-61-688-3939- E-mail address: kwseo08@kkpc.com• Supplier/Distributer information:- Company name:- Company name:- Address:- Dept.:- Telephone number:- Telephone number:- Fax number:- Fax number:- Telephone number:- Fax number:	- Address :	227 Yeosusandan 2-ro Yeosu-si Jeollanam-do, Korea
- Emergency telephone number: +82-61-688-3931~4- Fax number: +82-61-688-3939- E-mail address: kwseo08@kkpc.com• Supplier/Distributer information:- Company name:- Address:- Dept.:- Telephone number:- Telephone number:- Emergency telephone number:- Fax number:- Fax number:	- Dept. :	Production Technology Team
number: +82-61-688-3931~4- Fax number: +82-61-688-3939- E-mail address: kwseo08@kkpc.com• Supplier/Distributer information- Company name:- Address:- Address:- Dept.:- Telephone number:- Emergency telephone:number:- Fax number:	- Telephone number :	+82-61-688-3920
- E-mail address: kwseo08@kkpc.com• Supplier/Distributer information- Company name:- Company name:- Address:- Dept.:- Telephone number:- Emergency telephone:number:- Fax number:		+82-61-688-3931~4
• Supplier/Distributer information - Company name : - Address : - Dept. : - Telephone number : - Emergency telephone : number : - Fax number :	- Fax number :	+82-61-688-3939
- Company name:- Address:- Dept.:- Telephone number:- Emergency telephone number:- Fax number:	- E-mail address :	kwseo08@kkpc.com
- Address:- Dept.:- Telephone number:- Emergency telephone number:- Fax number:	Supplier/Distributer information	ation
- Dept. : - Telephone number : - Emergency telephone . number . - Fax number :	- Company name :	
- Telephone number : - Emergency telephone number : - Fax number :	- Address :	
- Emergency telephone number - Fax number :	- Dept. :	
number - Fax number :	- Telephone number :	
	- Fax number :	
- E-mail address :	- E-mail address :	

- Chronic aquatic toxicity : Category2

B. GHS label elements

• Hazard symbols



- Not applicable

 \circ Hazard statements

- H411 Toxic to aquatic life with long lasting effects

• Precautionary statements

1) Prevention

- P273 Avoid release to the environment.

2) Response

- P391 Collect spillage.

3) Storage

- Not applicable

4) Disposal



- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

• NFPA grade (0 ~ 4 level)

- Health : 0, Flammability : 1, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Styrenated phenol	Phenol, styrenated	61788-44-1	98.9
Stabilizer	-	-	<1
Phenol	Hydroxybenzene	108-95-2	<0.1

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15minutes and call a doctor/physician.

B. Skin contact

- Flush skin with plenty of wter for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Move containers from fire area, if you can do without the risk.
- Cool containers with water until well after fire is out.
- Keep unauthorized personnel out.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.



A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Prevent the influx to waterways, sewers, basements or confined spaces.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Comply with all applicable laws and regulations for handling
- Get the manual before use.
- Dealing only with a well-ventilated place.
- Do not inhale the steam prolonged or repeated.

B. Conditions for safe storage, including any incompatibilities

- Do not apply direct heat.
- Keep in the original container.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Keep sealed when not in use.
- Prevent static electricity and keep away from combustible materials or heat sources.
- Collected them in sealed containers.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

• ACGIH TLV

- [Phenol] : TWA 5 ppm (19 mg/m3)

o OSHA PEL

- [Phenol] : TWA 5 ppm (19 mg/m3)

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Personal protective equipment

Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.



- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

\circ Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

Hand protection

- Wear appropriate glove.

 \circ Skin protection

- Wear appropriate clothing.

 \circ Others

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	Pale yellow
B. Odor	Not available
C. Odor threshold	Not available
D. pH	7
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	310~313°C
G. Flash point	182 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not applicable
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	59 mg/l @ 20 °C
M. Vapour density	Not available
N. Specific gravity(Relative density)	1.0816
O. Partition coefficient of n-octanol/water	log Pow > 4 @ 22 °C
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	300-600 (25 °C)
S. Molecular weight	220

10. STABILITY AND REACTIVITY

A. Chemical Stability and Reactivity

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure



- (Respiratory tracts)
 - Not available
- o (Oral)
 - Not available
- (Eye∙Skin)
 - Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

• Acute toxicity

* Oral

- [Styrenated phenol] : LD50 = 2500 mg/kg Rat
- [Phenol] : LD50 317 mg/kg Rat

* Dermal

- [Styrenated phenol] : LD50 > 7940 mg/kg Rabbit
- [Phenol] : LD50 670 mg/kg Rat
- * Inhalation
 - [Styrenated phenol] : LC50 > 158.31 mg/L/4hr Rat (ECHA)
 - [Phenol] : dust LC50 0.316 ${\rm mg}/\ell$ Rat
- Skin corrosion/irritation
 - Not available
- \circ Serious eye damage/irritation
 - Not available

Respiratory sensitization

- Not available
- \circ Skin sensitization
 - Not available
- Carcinogenicity
 - * IARC
 - [Phenol] : Group 3
 - * OSHA
 - Not available
 - * ACGIH
 - [Phenol] : A4
 - * NTP
 - Not available
 - * EU CLP
 - Not available
- Germ cell mutagenicity
 - Not available
- Reproductive toxicity
 - Not available
- \circ STOT-single exposure
 - Not available
- \circ STOT-repeated exposure
 - Not available
- Aspiration hazard
 - Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- Fish
 - [Styrenated phenol] : LC50 = 1 ~ 10 mg/\ell 96 hr
 - [Phenol] : LC50 10.9 mg/ℓ 96 hr
- \circ Crustaceans
 - [Styrenated phenol] : EC50 = 4.6 $\, \mathrm{mg}/\ell$ 48 hr Other
 - [Phenol] : LC50 3.1 mg/ℓ 48 hr
- Algae
 - [Styrenated phenol] : EC50 = 9.7 mg/ ℓ 72 hr Other



- [Phenol] : EC50 370 mg/ℓ 96 hr

B. Persistence and degradability

- Persistence
 - [Styrenated phenol] : log Kow > 4
 - [Phenol] : log Kow 1.46
- Degradability
 - Not available

C. Bioaccumulative potential

- \circ Bioaccumulative potential
 - [Styrenated phenol] : BCF = 18.21
- \circ Biodegration
 - [Styrenated phenol] : 7% (28days) (OECD 301, GLP)
 - [Phenol] : 85 (%)

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designated waste is mixed, it is difficult to treat separately, then can be reduction or stabilization by incineration or similar process.

- If water separation is possible, pre-process with Water separation process.

- Dispose by incineration.
- Will be pre-processed by the separation of oil and water.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.

- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG and DOT)

- 3082

B. Proper shipping name

- Environmentally hazardous substances, liquid, n.o.s. (Styrenated phenol)

C. Hazard Class

- 9

D. IMDG and DOT Packing group

- Ш

E. Marine pollutant

- Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-A (General fire schedule)
- EmS SPILLAGE SCHEDULE : S-F (Water-soluble marine pollutants)



```
15. REGULATORY INFORMATION
   A. National and/or international regulatory information
      • POPs Management Law
          - Not applicable
      • Information of EU Classification
          * Classification
             - [Phenol] : Muta.Cat.3; R68 T; R23/24/25 Xn; R48/20/21/22 C; R34
          * Risk Phrases
             - [Phenol] : R23/24/25, R34, R48/20/21/22, R68
          * Safety Phrase
             - [Phenol] : S1/2, S24/25, S26, S28, S36/37/39, S45
      ◦ U.S. Federal regulations
          * OSHA PROCESS SAFETY (29CFR1910.119)
             - Not applicable
          * CERCLA Section 103 (40CFR302.4)
             - [Phenol] : 453.599 kg 1000 lb
          * EPCRA Section 302 (40CFR355.30)
             - [Phenol] : 226.7995/4535.99 kg 500/10000 lb
          * EPCRA Section 304 (40CFR355.40)
             - [Phenol] : 453.599 kg 1000 lb
          * EPCRA Section 313 (40CFR372.65)
             - [Phenol] : Applicable

    Rotterdam Convention listed ingredients

          - Not applicable
      • Stockholm Convention listed ingredients
          - Not applicable
      • Montreal Protocol listed ingredients
          - Not applicable
```

16. OTHER INFORMATION

A. Reference

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2015-05-19

C. Revision number and Last date revised

- 2 times, 2018-08-30

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).